(X32-4030-02) CD PLAYER UNIT

(T25-0204-05) OPTICAL PICKUP

IC1 : AN8806SB
IC2 : MN662720RB
IC3 : 78002GC-603-AB8
IC4 : BA6398FP
IC5 : NJM4565MD

Q1, 2 : 2SA1362(Y)
Q3 : 2SA1037K
Q4 : DTC124EK or XDC124EK
Q5 : DTA124EK or XDC124EK

D1, 4~6 : MA110
D2, 3 : B30-1426-05
PH1, 2 : PT461T

SIGNAL LINE
GND LINE
+B LINE

DTA114EK DTA124EK
DTC124EK XDA124EK
XDC124EK 2SA1037K
2SA1362 2SC2412K
2SD2114K

2SD1119 2SB941 TA7288P NJM4565MD TA78L05F S-80737AN-D1 75112GF-E63-3BE 78002BGC603-AB8 M5278D05 BA

IC1 : AN8806SB
IC2 : MN662720RB
IC3 : 78002GC-603-AB8
IC4 : BA6398FP
IC5 : NJM4565MD

Q1, 2 : 2SA1362(Y)
Q3 : 2SA1037K
Q4 : DTC124EK or XDC124EK
Q5 : DTA124EK or XDC124EK

D1, 4~6 : MA110
D2, 3 : B30-1426-05
PH1, 2 : PT461T

(X29-4040-00) CONTROL CIRCUIT UNIT

IC2 SERVO PROCESSOR (BOTTOM VIEW)

IC3 MECHA μ-COM (BOTTOM VIEW)

IC4 MOTOR DRIVER

IC3 SYSTEM μ-COM

IC5 TE AMP

IC5 μ-COM RST IC

UP, DOWN MOTOR

DSPS

PH1

MI-SW S1

MG-SW S2

EJECT-SW S3

THERMAL SHUT DOWN SW

SW 1 SLED-SW

5V SW

Q5 DRIVE

LOADING MOTOR

CN2 (E39-0042-05)

CN3 (E39-0041-05)

(X13-8640-00)

TA78L05F

S-80737AN-D1

75112GF-E63-3BE

78002BGC603-AB8

M5278D05

BA6398FP

MN662720RB

AN8806SB

CAUTION : F
list). ⚠ Indica
out (exposed p

- DC voltages
or/and units

(X29-4040-00) CONTROL CIRCUIT UNIT

IC1	: M5278D05
IC2	: TA78L05F
IC3	: 75112GF-E63-3BE
IC4	: TA7288P
IC5	: S-80737AN-D1
IC6	: AK4318-VS
IC7	: NJM4565MD
Q1,3,7,11,12,16	: DTC124EK or XDC124EK
Q2	: DTA114EK
Q4,10	: DTA124EK or XDA124EK
Q5	: 2SB941
Q6	: 2SC2412K
Q8	: 2SA1362(Y)
Q9	: 2SD1119
Q13, 14	: 2SD2114K
Q15	: 2SA1037K
D1, 5	: MA8091-M
D2, 6, 7, 11	: MA8056-M
D3	: DA204K
D4,13	: ERA15-01 or AM01Z
D8, 9	: MA110
D10	: MA8075-M
D11	: MA8062-M
D12	: DAP202K
TH1	: NTH5G40B333K01
PH1	: NJL5183KA-F20

E56-0805-15

(1) REQ H
(2) GND
(3) BU+14V
(4) CH-CON
(5) CH-MUTE
(6) A-GND
(7) CH-RST
(8) R-CH
(9) REQC
(10) DATAC
(11) DATAH
(12) L-CH
(13) CH-CLK

CN1(E56-0805-15)

MN662720RB





AN8806SB



CAUTION : For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list). ⚠ Indicates safety critical components. To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.

- DC voltages are as measured with a high impedance voltmeter. Values may vary slightly due to variations between individual instruments or/and units.

Y22-5230-62

KDC-C603

KENWOOD